



# **FEATURES & SPECIFICATIONS**

# HB-1230CE

#### **ZERO TURN RADIUS**

Maneuver quickly and easily through congested work sites, through doorways and around tight corners.

## PROPORTIONAL LIFT AND DRIVE

User-friendly joystick control offers smooth lift and speed control.

# LARGE WORK PLATFORM

Includes 76.2 cm slide out deck extension for extra supplies and manpower, extension is supported midrail to eliminate jams.

#### MAINTENANCE FREE

Maintenance free AGM Batteries and easy access panels improve life cycle and cost of ownership.

#### **LOW FLOOR LOADING**

Lightweight design makes the lift easy to manuver and allows for use on delicate or sensitive surfaces.

## **USER-FRIENDLY DESIGN**

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

#### **ROBUST RAIL SYSTEM**

Unique rail technology provides greater durability and resilience against wear on the job site.

## **OVERSIZED 3.18 CM PINS**

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

# **NON-MARKING WHEELS**

Protect sensitive floors and prevent surface scuffs on job site.

#### NON-SKID DECK

Large durable platform provides ample working room.





HEIGHTS METRIC  Working Height 5.7 m  Platform Height Max 3.7 m	
Platform Height Min 50.8 cm	
Ground Clearance Raised 1.3 cm	
Ground Clearance Lowered 7.3 cm	
MEASUREMENTS	
Overall Length 157.5 cm	
Overall Width 76.2 cm	
Stowed Height 162.6 cm	
Platform Length 134.6 cm	
Platform Width 64.8 cm	
Platform Extension 76.2 cm	
PERFORMANCE	
Platform Capacity 249.5 kg	
Rated Occupancy 1 person	
Extension Capacity 113.4 kg	
Weight 730.3 kg	
Gradeability 25%	
Inside Turn Radius Zero	
Drive Speed Raised 0.3 m/s	
Drive Speed Lowered 1.0 m/s	
Lift Speed Up/Down 18/16 sec	
Power Source (2) 12V DC	
Tires Front/Rear 20.3/30.5 cm	
FLOOR LOADING	
Min Wheel Load 707.8 kPa	
Max Wheel Load 949.6 kPa	
Min Machine Load 6.6 kPa	
Max Machine Load 8.9 kPa	

#### 1-866-334-0756 // WWW.HYBRIDLIFTS.COM